

NUKEPROOF DISSENT 275 GEOMETRY CHART

FRAME SIZE	SMALL	MEDIUM	LARGE	X-LARGE
(ST) SEATTUBE LENGTH	405MM / 16"	405MM / 16"	405MM / 16"	405MM / 16"
(TTE) EFFECTIVE TOP TUBE LENGTH	590.6MM	610.6MM	630.6MM	650.6MM
(HT) HEADTUBE LENGTH	110MM	110MM	110MM	110MM
(HA) HEADTUBE ANGLE	63°	63°	63°	63°
(WB) WHEELBASE	*1221.5MM (MIDDLE SETTING)*	*1241.5MM (MIDDLE SETTING)*	*1261.5MM (MIDDLE SETTING)*	*1281.5MM (MIDDLE SETTING)*
(CS) CHAINSTAY LENGTH	435/440/445MM	435/440/445MM	435/440/445MM	435/440/445MM
(STE) EFFECTIVE SEATTUBE ANGLE	74.5°	74.5°	74.5°	74.5°
(BB) BOTTOM BRACKET DROP	0MM	0MM	0MM	0MM
BOTTOM BRACKET HEIGHT	357.5MM	357.5MM	357.5MM	357.5MM
(RE) REACH	425MM	445MM	465MM	485MM
STACK	598.4MM	598.4MM	598.4MM	598.4MM
FORK TRAVEL	200MM	200MM	200MM	200MM
FORK OFFSET	46MM	46MM	46MM	46MM
AXLE TO CROWN	585MM	585MM	585MM	585MM